

**Professional
cleaning
detergents**
Selection Guide

www.electroluxprofessional.com

Electrolux Professional Genuine detergents

**With Electrolux Professional
detergents we take care of the
Environment, People and your
Equipment:**

Our products ensure the best performance and highly effective cleaning solutions with perfect balance between equipment and detergents.

We guarantee appliances' longevity by means of intensive and accurate laboratory testing, always ensuring perfect cleaning results as well as the highest performance of the equipment and its components.

We have developed ecofriendly detergents with high quality raw material and low environmental impact, which are able to avoid glass wear and extend textile life. All Electrolux Professional detergents are over 95% biodegradable fulfilling the strictest regulations on the global market and complying with REACH regulation; moreover, our internal Restricted Material List is even more severe to provide you the safest solution.

Furthermore, discover our brand-new ECOLABEL and NORDIC SWAN products developed to be effective and safe for the environment





Index

Detergents for coffee machines	page 5	Surface cleaning detergents	page 31
Detergents for food segment		Water Treatment	
Ovens Solid detergents	page 10	Automatic water softeners	page 36
Ovens Liquid detergents	page 11	Manual water softeners	page 39
Dishwashing detergents	page 12	Water softeners consumables	page 40
The right solution	page 14	Water treatment	page 41
Tools & Tips for Technicians	page 16	Water treatment with reverse osmosis system	page 44
SpeedDelight detergent	page 18		
Degreaser	page 19	Pumps for detergents	
Detergents for laundry segment		Pumps for food segment	page 46
lagoon® Advanced Care	page 22	Pumps for laundry segment	page 48
Pre-spotting agents	page 23		
Washers & Dryers Ecolabel range	page 24	Installation material for laundry	
Washers & Dryers Nordic Swan range	page 25	Hoses and interfaces	page 54
		Cables, connections	page 55
Descaling detergents		Safety at a glance	page 56
C30 Multipurpose descaler	page 29		
C25 Rinse & Descale Tab	page 30		





Detergents for coffee machines

Index

U01 Cleaning Tabs for Espresso Machine	page 6
U02 Cleaning Tabs for Standard Espresso Machines	page 7
U03 Milk Frother Cleaner	page 7



Purchase our detergents and accessories
at electroluxprofessional.com

Coffee machines detergents

We recommend you to clean your machine daily to save both power and help you avoid costly repairs. By doing a little bit of daily maintenance and a regular deep clean, you can prevent the building up of back pressure on your pump and make the element work far more effectively.

Use these items to clean your coffee machine.



Code OSPO27

U01 Cleaning Tabs for Espresso Machines

- Removes coffee residuals and oils in super-automatic Espresso machines
- Facilitates the cleaning of the equipment
- Ensures efficient and extended working of the machine
- Formulated to dissolve in super-automatic cleaning cycles
- A convenient portion for easy and controlled dosing
- Improves flavour and aroma of espresso after the machine is cleaned
- 120 tabs of 2.4g



Code 0SPO28



U02 Cleaning Tabs for Standard Espresso Machines


- Removes coffee residuals and oils in Standard Espresso machines
- Facilitates the cleaning of the equipment
- Ensures efficient and extended working of the machine
- A convenient portion for easy and controlled dosing
- Improves flavour and aroma of espresso after the machine is cleaned
- 100 tabs of 1g



Code 0SPO29

U03 Milk Frother Cleaner

- Removes deposits that occur from milk steaming and frothing
- For use in autofrothers, steam wands & frothing pitchers
- Ensures efficient and extended working of the machine
- Comes in a dual-chamber 1L bottle that contains a built-in measuring device
- Delivers over 30 uses per bottle
- 1 Lt bottle







Detergents for food segment

Index

Ovens

Ovens Solid detergents	page 10
Ovens Liquid detergents	page 11

Dishwashing

Dishwashing detergents	page 12
The right solution	page 14
Tools & Tips for Technicians	page 16

Speedelight detergent	page 18
-----------------------	---------

Degreaser	page 19
-----------	---------



Purchase our detergents and accessories
at electroluxprofessional.com

Ovens Solid detergents

Solid detergents ideal for all type of cooking and demanding sites. SkyClean is an automatic and built-in self cleaning system with integrated descaling of the steam generator



Code 0S2395

C22 Cleaning tab

- ▶ Effective cleaning tab for ovens with integrated washing cycles.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 100 tabs bucket; 65 gr. each



Code 0S2394

C25 Rinse & Descale Tab

- ▶ Effective rinse&descale tab for ovens with integrated washing cycles.
- ▶ For a fast drying with a perfectly shining cavity and a descaled boiler.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 50 tabs buckets; 30 gr. each



Usage table

Type of dirt	number of C22 Cleaning tabs		number of C25 Rinse&Descale	
	6GN/10GN	20 GN	6GN/10GN	20 GN
soft	1	2	1	2
medium	2	3	1	2
strong	3	4	1	2
extra strong	4	6	1	2



Up to -15%* of running cost: savings on energy, water, detergent and rinse aid

the use of original detergents ensures ideal performance and durability of your oven.

* calculated using SkyClean function versus equivalent cleaning cycle on previous Electrolux Professional oven range. Data available in April 2019.

Ovens Liquid detergents

Code 0S2282

C20 Extra Strong Detergent for Ovens

- ▶ High degreasing power for ovens with integrated washing cycle
- ▶ **Environmental friendly chemical with revised formula without EDTA**
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Intensively field tested by Experts and Customers
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download
- ▶ Ergonomic packaging with n.2 x 5 liter jugs for easy handling and stocking



Code 0S2283

C21 Extra Strong Rinse Aid for Ovens

- ▶ Quick drying and perfect shining cavity for ovens with integrated washing cycle
- ▶ Eco friendly chemical with low environmental impact by use of vegetable origin surfactants
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Intensively field tested by Experts and Customers
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download
- ▶ Ergonomic packaging with n.2 x 5 liter jugs for easy handling and stocking



Accessories for liquid chemicals



Code 0S2347

Wall mounted holder for detergent tank

- ▶ Ideal to keep detergents away from the floor



Code 0S2559

Open base hanging holder

- ▶ Ideal to keep detergents away from the floor



Code 922618

Connection kit

- ▶ External connection kit for liquid detergent/rinse aid

Maximize your kitchen

Flexible, hygienic and safe installation, cooking and handling thanks to over 200 different dedicated accessories and consumables to help you make the most of your SkyLine oven



Scan to discover
our accessories and consumables



Dishwashing detergents

To get the **best washing results**, you need to choose not only the **right machine** and matching the proper **water treatment system**, but also to select the **specific detergent and rinse aid**. To provide our customers the **most specific solution** for every need, we have developed two couples of detergents and a selection guide that can be found on the next pages.

All our dishwashing detergents have controlled foaming properties and have demonstrated excellent results when compared to currently distributed commercial brands.

Furthermore, by using genuine Electrolux Professional detergents, the life of the glasses is extended since they are not worn by the chemical aggression of a standard detergent and rinse aid (see testing results on pag.13).



Code 0S2092

C11 Detergent for Dishwashers

- ▶ Concentrated formula for reduced consumption
- ▶ Ideal for all types of crockery: ceramic, porcelain, glass, crystal and metal
- ▶ Its delicate aroma helps minimize the unpleasant odor which can sometimes be found in dishwashers
- ▶ Highly recommended for restaurants preparing fish and sea food
- ▶ Particularly suitable for hard and medium hard water
- ▶ Intensively field tested by Experts and Customers
- ▶ Low environmental impact with reduced carbon footprint
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking



ECO friendly

Code 0S2094

C12 Rinse Aid for Dishwashers

- ▶ Concentrated formula for reduced consumption
- ▶ Ideal for all types of crockery: ceramic, porcelain, glass, crystal and metal
- ▶ Removes lime scale from dishes, leaving a perfect bright surface
- ▶ Reduced appliance lime scale deposit
- ▶ Guarantees sparkling clean and dry crockery
- ▶ Perfect drying results guaranteed, without manual actions
- ▶ Particularly suitable for hard and medium hard water
- ▶ Intensively field tested by Experts and Customers
- ▶ Eco friendly chemical with low environmental impact by use of vegetable origin surfactants
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking



ECO friendly



ECO friendly



Code 0S2093

C13 Eco Detergent for Dishwashers

- ▶ Highly concentrated and Ecofriendly formula without EDTA, NTA and polyphosphates
- ▶ Ideal for all type of crockery: ceramic, porcelain, glass, crystal and metals
- ▶ Particularly suitable for soft water
- ▶ Very efficient in case of dried food residues on all kind of dishes
- ▶ Intensively field tested by Experts and Customers
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Eco friendly detergent with low environmental impact and reduced carbon footprint
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking


Code 0S2904

C15 Eco Rinse Aid for Professional Dishwashers


- ▶ Ideal for all types of crockery: ceramic, porcelain, glass, crystal, metal and plastic
- ▶ Neutral pH
- ▶ Removes lime scale from dishes, leaving a perfect bright surface
- ▶ Reduced appliance lime scale deposit
- ▶ Guarantees sparkling clean and dry crockery
- ▶ Perfect drying results guaranteed, without manual actions
- ▶ Particularly suitable soft and osmotized water
- ▶ Intensively field tested by Experts and Customers
- ▶ Eco friendly detergent with low environmental impact by use of vegetable origin surfactants
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking

Did you know that your glasses loose “weight” each cycle and become more and more fragile?


Soda-lime (the most common glass)



Crystal (crystal glass)



Lead crystal (best quality glass)



◆ Glass weight loss using Electrolux Professional recommended solutions
◆ Glass weight loss using standard chemicals

Code 0S2362

C30 Multipurpose descaler



- ▶ Effectively eliminates encrustations and scale from washing appliances and boilers of any professional equipment
- ▶ The regular use of C30 Multipurpose descaler keeps the equipment always efficient, while slowing down the natural wear and tear
- ▶ Thanks to its low foaming power, C30 Multipurpose descaler is recommended for cleaning boilers and equipment with an automatic descaling device
- ▶ The neutral fragrance makes its use more pleasant
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking

The right solution

1	2	3	4	5
What are you going to wash?	Water hardness (°F) *	Recommended water treatment	Water hardness after treatment (°F) *	Detergent to be used
 Glasses and crystals	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 C13 Eco Detergent for Dishwashers  C15 Eco Rinse Aid for Professional Dishwashers
	Medium Soft 7 ÷ 15	For crystals use total demineralization (refer to the chart on the right for the proper solution for your machine)		
	Medium Hard 15 ÷ 25	For crystals use total or partial demineralization while for standard glasses use water softener (refer to the chart on the right for the proper solution for your machine)	Medium to Hard 7 ÷ 25	 C11 Detergent for Dishwashers  C12 Rinse Aid for Dishwashers
	Hard / Very Hard 25 ÷ 45	For standard glasses use water softener while for crystals use water softener plus reverse osmosis (refer to the chart on the right for the proper solution for your machine)		
 Cups and mugs	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 C13 Eco Detergent for Dishwashers  C15 Eco Rinse Aid for Professional Dishwashers
	Medium Soft 7 ÷ 15			
	Medium Hard 15 ÷ 25	Partial demineralization (refer to the chart on the right for the proper solution for your machine)	Medium to Hard 7 ÷ 25	 C11 Detergent for Dishwashers  C12 Rinse Aid for Dishwashers
	Hard / Very Hard 25 ÷ 45	Water softener (refer to the chart on the right for the proper solution for your machine)		
 Plates and cutlery	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 C13 Eco Detergent for Dishwashers  C15 Eco Rinse Aid for Professional Dishwashers
	Medium Soft 7 ÷ 15	Water softener is optional		
	Medium Hard 15 ÷ 25	Water softener (refer to the chart on the right for the proper solution for your machine)	Medium to Hard 7 ÷ 25	 C11 Detergent for Dishwashers  C12 Rinse Aid for Dishwashers
	Hard / Very Hard 25 ÷ 45			
 Stainless Steel Pots	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 C13 Eco Detergent for Dishwashers  C15 Eco Rinse Aid for Professional Dishwashers
	Medium Soft 7 ÷ 15			
	Medium Hard 15 ÷ 25		Medium to Hard 7 ÷ 25	 C11 Detergent for Dishwashers  C12 Rinse Aid for Dishwashers
	Hard / Very Hard 25 ÷ 45	Water softener (refer to the chart on the right for the proper solution for your machine)		

		  Undercounter/ Glasswasher	  Hood Type Dishwasher	  Pot&Pan Washer	  Single&Compact Rack Type with ESD	  Single&Compact Rack Type	  Multi Rinse Rack Type
Manual Water Softener	OS1074 (cold) 8 lt with bypass	•	•	•			
	OC1903 (cold) 8 lt without bypass	•	•	•			
	OS1076 (cold) 12 lt with bypass	•	•	•			
	860412 (cold) 12 lt without bypass	•	•	•			
	860430 (cold) 20 lt	•	•	•			
Automatic Water Softener	860413 (cold) 8 lt	•	•	•			
	OS1946 (cold) 8 lt	•	•	•			
	OS1079 (cold) 8 lt	•	•	•			
	002454 (cold) 8 lt	•	•	•			
	OS1083 (cold) 12 lt	•	•	•			
	865495 (hot) 12 lt			•			
	OS1089 (cold) 24 l	•	•	•			
	PNC 865284 2x13 lt (cold) + 12 lt (hot&cold)				•		•
	865284 (hot&cold) 12 lt				•	•	•
Partial Demineralization	864017 (hot or cold)	•	•				
Total Demineralization	864367 (hot or cold)	•	•				
Osmosis	864388	•	•				
	865494 (hot&cold - WS or cold RO)						•

Tools & Tips for Technicians

Before you head out to your customer, make sure to have the right tools with you.

1

To measure water hardness you need



OS1701
Carbonate and total hardness test



OS2916
Carbonates chemical analysis; 100 test sticks

2

To verify the pH you need:



OS0481
Laboratory pH meter: PH/EC/TDS meter; HI9812; 100ml



OS2245
Portable pH meter

don't forget also:



OS2383
solution to preserve electrodes



OS2255
spare electrode for OS2245 pH meter



OS2246
Solution pH 7.01



OS2247
Solution pH 4.01



OS2248
Solution pH 5.25



OS1707
TDS solution for calibrating electrodes

3

You may also need:



OS0585
TT chloride test kit chemical kit

OS2917
Iron chemical analysis; 100 test sticks 2383

4

Also available a kit with main components:





OS2956
Water analysis box LAB KIT



OS2957
Water analysis box BASIC KIT


How to determine detergent concentration from conductivity Measurement from hot water

- ▶ First of all, we strongly suggest to measure water hardness
- ▶ Set the dosages according to water hardness and product technical data sheets
- ▶ After the first detergent load, pick up from the water tank 300ml of hot water (around 60°C)
- ▶ Immerse the conductivity/pH meter in the solution and wait about a minute to let the value stabilize.
- ▶ Pay attention to the unit of measurement shown by the instrument (1 mS corresponds to 1000 μ S)
- ▶ Refer to the chart or the picture and find out to the dosage in ml/L starting from the conductivity (μ S/cm) you have identified.
- ▶ If necessary, reset the dosing pump and check after 10 washing cycles.



Conductivity VS Concentration Chart

Dosage ml/L	Conductivity μ S/cm using C11 Detergent	Conductivity μ S/cm using C13 Detergent
0	590	590
0,5	700	750
1	930	1100
1,5	1250	1670
2	1690	2200
3	2500	3200
4	3300	4300
5	4100	5400



SpeeDelight detergent



Code 0S2292

C41 Hi-temp Rapid Degreaser

- ▶ Specifically developed formula to use with SpeeDelight and Hot Surfaces
- ▶ Best cleaning performance at high temperature, protecting glass, silicon and stainless steel
- ▶ Food safe detergent
- ▶ Makes daily cleaning easier and faster, removing all type of carbonized residuals
- ▶ Intensively field tested by Experts and Customers
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download
- ▶ N. 6 x 1 liter bottles with practical nozzle, including an extra spraying unit



Tutorial video



Follow the cleaning path with Electrolux Professional

Watch the video tutorial SpeeDelight cleaning

Degreaser



Code 0S1841

C40 Degreaser for Hot Surfaces

- ▶ **Recommended for fry tops and braising pans with mild steel or chromed surfaces**
- ▶ Best cleaning performance at high temperature (**165°C – 175°C**), without damaging cooking surfaces
- ▶ **Food safe detergent**
- ▶ Makes daily cleaning easier and faster, removing all type of carbonized residuals
- ▶ Eliminates the risk of food cross-contamination
- ▶ Intensively field tested by Experts and Customers
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download
- ▶ Packaging consisting of n.6 x 1 liter bottles with practical nozzle, including an extra spraying unit

Tutorial video



Follow the cleaning path with Electrolux Professional







Detergents for laundry segment

Index

lagoon® Advanced Care	page 22
Pre-spotting agents	page 23
Washers & Dryers Ecolabel range	page 24
Washers & Dryers Nordic Swan range	page 25



Purchase our detergents and accessories
at electroluxprofessional.com

lagoon® Advanced Care

Electrolux Professional lagoon® Advanced Care system is delicate on fabrics, gentle on the environment, and a game changer for the business. It is the only wet-cleaning system capable of offering excellent cleaning results in a truly sustainable way, with the same seamless handling and high productivity of a dry cleaning process.



Code 0W7095 - PNC 432731085 (20 lt tank) / Code 0W7096 - PNC 432731086 (10 lt tank)

W01 - lagoon® Sensitive Detergent

Detergent for use in professional wet cleaning, with the appropriate Electrolux Professional lagoon® wet cleaning programs and together with W03 - lagoon® Sensitive Conditioner.



Code 0W7099 - PNC 432731089 (20 lt tank) / Code 0W709A - PNC 432731090 (10 lt tank)

W02 - lagoon® Delicate Detergent

Detergent for use in professional wet cleaning. With the appropriate Electrolux Professional lagoon® wet cleaning programs for mixed fibers and together with W03 - lagoon® Sensitive Conditioner. Suitable for washing colored textiles at 40 °C.



Code 0W7097 - PNC 432731087 (20 lt tank) / Code 0W7098 - PNC 432731088 (10 lt tank)

W03 - lagoon® Sensitive Conditioner

Conditioner for use in professional wet cleaning. With the appropriate Electrolux Professional lagoon® wet cleaning programs and together with W01 - lagoon® Sensitive Detergent for delicate fibers. Suitable for robust fabrics together with W02 - lagoon® Delicate Detergent.

Complete
range of smart
detergents for
unprecedented
results.



Pre-spotting agents



Code 0W709B - PNC 432731091
(1 pack of two 5 lt tanks)

A01 - lagoon® Pre-treatment

Universal mild prebrushing agent to use in professional wet cleaning. Can be applied as pre-treatment on any type of fiber.



Code 0W709E - PNC 432731094
(1 pack of six 0.5 lt bottles)

P01 - lagoon® Protein Stain Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on stains caused by blood, egg, milk, vomit and urine.



Code 0W709C - PNC 432731092
(1 pack of six 0.5 lt bottles)

P02 - lagoon® Tannin Stain Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on stains caused by fruits, coffee, tea, red wine and grass.



Code 0W709D - PNC 432731093
(1 pack of six 0.5 lt bottles)

P03 - lagoon® Grease Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on stains caused by waxes, polishes, oils, greases and make-up.



Code 0W709F - PNC 432731095
(1 pack of six 0.5 lt bottles)

P04 - lagoon® Ink Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on synthetic stains, stains caused by inks, adhesives, lacquers, synthetic paints and tar.



Code 0W7LLV - PNC 432731110

Starter kit

contains 4x0.5L of P01, P02, P03, P04
The perfect solution to have the chance to test our spotting agents

Special purpose products



Code 0W709K - PNC 432731099
(1 pack of two 5 lt tanks)

A02 - lagoon® Colour Transfer Reducer

Colour fixing and levelling agent for direct dyes on textiles. Helps to reduce risk of colour transfer in Electrolux Professional lagoon® wet cleaning programs.



Code 0W7Q1A - PNC 432731148
(1 pack of one 10 lt tank)

A03 - lagoon® Leather Care

Conditioner oil to restore natural leather appearance with nurturing and softening effect while balancing the colour.



Code 0W7RW6 - PNC 432731156

lagoon® Leather & Shoe Cleaning Starter - Kit

The kit consist of all tools that ensure basic and advanced treatment of leather textiles in the lagoon® Advanced Care - cleaning process

Washers & Dryers

The new range of Laundry detergents has been developed to offer high quality, safety and effectiveness ensuring a low environmental impact thanks to reduced water pollution, waste production and energy consumption compared to standard product on the market. Electrolux Professional commitment is guaranteed by **ECOLABEL** and **NORDIC SWAN** certification and approval. Furthermore, our range has been formulated to reduce at minimum the risk of sensitization to provide safe and effective detergents for all users up to the final customer wearing a textile washed with **HYPOALLERGENIC** and **DERMATOLOGICALLY TESTED** products*.



Code 0W7Y6G
PNC 432731829
(20 lt tank)

L00 – Laundry Eco Degreaser

An efficient surfactant degreaser very active on animal fats and vegetable oils. Suitable for restaurant linen, work wear, and for treatment of stubborn oily stains. Use it in addition to L02 and L03.



Code 0W7RBB
PNC 432731139
(15 kg bag)

L01 – Laundry Eco Powder

High-performance powder detergent allowing a perfect cleaning with a minimum dose. Removes grease and stains protecting fabrics and colors. Lightly scented.



Code 0W7RBC
PNC 432731140
(20 lt tank)

L02 – Laundry Eco Wash

Liquid detergent for all linen, with strong efficacy even at 30°C and low doses. Respects textile fibers and colours by giving them back the original luster.



Code 0W7RBF
PNC 432731143
(20 lt tank)

L03 – Laundry Eco Booster

In case of difficult soil and in presence of hard/very hard water, L03 Laundry Eco Booster ensures high standard performances. Use it in combination with L01 or L02 detergents.



Code 0W7RBD
PNC 432731141
(20 lt tank)

L04 – Laundry Eco Bleach

New generation of bleaching agent, effective even at 30°C while preserving textiles quality and colors.



Code 0W7RBE
PNC 432731142
(20 lt tank)

L05 – Laundry Eco Softener

Slightly scented softener for pleasant textiles, easy ironing and with no residuals of static electricity.

*L00 – Laundry Eco Degreaser is still under testing, the rest of the range have already completed the tests with positive results



Satisfying the requirements of the **EUROPEAN ECOLABEL** means respecting very strict specifications on raw materials, high performance criteria and rigorous environmental-friendly approach.

The EU Ecolabel helps you identify products and services that have a **reduced environmental impact throughout their life cycle**, from the extraction of raw material through to production, use and disposal. Recognised throughout Europe, EU Ecolabel is a voluntary label promoting environmental excellence which can be trusted. Providing you a complete range of products including detergent, booster, softener and bleach reflects a strong commitment on the entire process.



Using our **NORDIC SWAN** products range means providing effective cleaning with the guarantee of a green process from raw material choices to performance tests, verified by an external auditing procedure.

The **Nordic Swan Ecolabel** is the official Ecolabel of the Nordic countries, a voluntary and positive practical tool for consumers to help them actively choose environmentally sound products. The Nordic Swan Ecolabel is an ISO 14024 type 1 Ecolabelling system and it is a third-party control organ. Products carrying the Nordic Swan Ecolabel meet extremely high environmental and often climate requirements.

The life-cycle perspective of the product is analysed, i.e., **the product's impact on the environment from raw material/source to waste.**

Criteria is also set with regard to quality, health aspects and performance/ functionality. Each product group has overriding general criteria requirements as well as product-specific requirements.



Code 0W7RBG - PNC 432731144 (20 lt tank)

L06 - Laundry Swan Wash

Strong detergent for the most stubborn stain. Phosphate and silicate free alkaline detergent for excellent stain removal. Effective even on garment and work wear.



Code 0W7RBH - PNC 432731145 (20 lt tank)

L07 - Laundry Swan Gentle Wash

Detergent for the most stubborn stain. Liquid detergent for all types of tissues even colored. Excellent soil and stain removal properties. Prevents "greying" of tissues.



Code 0W7RBI - PNC 432731146 (20 lt tank)

L08 - Laundry Swan Bleach

Peracetic base bleach. Provides outstanding bleaching performances. Acts also as an alkalinity neutralizer to bring your tissues back to a neutral pH.



Code 0W7RBJ - PNC 432731147 (20 lt tank)

L09 - Laundry Swan Softener

Softener for all textiles. Optimal softening effect, also at short cycle times; diminishes static electricity. Ensures fast drying and easy to be ironed textiles.

Maintain a high standard drying experience with a periodic cleaning of your tumble dryers thanks to a fast and easy descaling process allowing the Moisture Balance function sensors to act efficiently and also ensuring to remove any eventual soap/softener that could remain.



Code 0S2394

C25 Rinse & Descale Tab

The perfect combination of citric acid (*Acidum citricum*) together with our dedicated formula ensures a perfect removal of any limestone and/or soap and softener residuals. Dissolve 1 tab in 1 liter of water and rinse the tumble dryer. If necessary you can use the **scouring pad** (0W7PM8)







Descaling detergents

Index

C30 Multipurpose descaler	page 29
C25 Rinse & Descale Tab	page 30



Purchase our detergents and accessories
at electroluxprofessional.com

Descaling detergents



Code 0S2362

C30 Multipurpose descaler



- ▶ Effectively eliminates encrustations and scale from washing appliances, boilers and other professional equipment (dishwashers, ovens, pasta cookers, bain marie, washing machines etc.). Refer to the Product Data Sheet (PDS) for process details.
- ▶ The regular use of C30 Multipurpose descaler keeps the equipment always efficient, removing scale while slowing down the natural wear and tear
- ▶ Thanks to its low foaming power, C30 Multipurpose descaler is recommended for cleaning boilers and equipment with an automatic descaling device
- ▶ The neutral fragrance makes its use more pleasant
- ▶ 1 pack of two 5 lt tanks

**Take care of
your appliances
ensuring better
performances
and longevity
with dedicated
detergents**





Code 0S2394

C25 Rinse & Descale Tab



- ▶ Effective rinse&descale tab for ovens with integrated washing cycles.
- ▶ Dissolve 1 tab in 1 liter of water to clean tumble dryer's drum removing soap/softener residuals
- ▶ For a fast drying with a perfectly shining cavity and a descaled boiler.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 50 tabs buckets; 30 gr. each



The new solid oven descaler can be used even for a professional cleaning of tumble dryers' drum







Surface cleaning detergents

Index

S01 Stainless steel surface Cleaner	page 32
S02 Degreaser	page 33
S03 Hygienizer	page 33
S04 Glasses & Hard Surfaces Cleaner	page 33



Purchase our detergents and accessories
at electroluxprofessional.com

Surface Cleaning detergents



The selection of appropriate surface cleaning detergents for kitchen cleaning is critical in maintaining effective particulate or microbial control.

Concentrated detergents

up to 250 ready-to-use spray bottles from just 1L of **super concentrated** product



Code 0S2881

S01 - Stainless steel surface Cleaner

Electrolux Professional stainless-steel surface Cleaner is a highly concentrated detergent specially developed to degrease and descale stainless-steel surfaces in the kitchen. It also leaves a protective film behind which facilitates future cleaning.




Recommended Dose: 20ml per 500ml of water.
The bottle contains 1 liter.

Take care of
your appliances
and surfaces
ensuring better
performances
and longevity with
dedicated cleaners



Purchase our detergents
and accessories at
electroluxprofessional.com



Code 0S2882

S02 - Degreaser

Electrolux Professional Degreaser is a highly concentrated detergent to clean and remove grease from appliances, surfaces and floors.



Recommended Dose: 20ml per 500ml of water.
The bottle contains 1 liter.



Code 0S2883

S03 - Hygienizer

Electrolux Professional Hygienizer is a highly concentrated detergent for a deep clean of bowls, internal components of beverage appliances and all surfaces.



Recommended Dose: 20ml per 500ml of water.
The bottle contains 1 liter.



Code 0S2884


S04 - Glasses & Hard Surfaces Cleaner



Electrolux Professional is a concentrated cleaner for all washable surfaces, like as glass, mirror, marble, working tops, induction and cook top.

Recommended Dose: 20ml per 500ml of water.
The bottle contains 1 liter.







Water treatment

Index

Automatic water softeners	page 36
Manual water softeners	page 39
Water softeners consumables	page 40
Water treatment	page 41
Water treatment with reverse osmosis system	page 44

Providing the proper water treatment will:

- ▶ avoid the risk of altering the taste and appearance of your foods
- ▶ reduce scale build-up therefore de-liming is less frequent, thus resulting in additional savings in operating costs
- ▶ extend the life of your appliance
- ▶ guarantee lower maintenance costs

Electrolux Professional suggests you to check your water quality in order to choose the right water treatment solution:

- ▶ water softener for high concentration of calcium
- ▶ water nanofilter or reverse osmosis filter for high concentration of calcium and chloride



Purchase our detergents and accessories at electroluxprofessional.com

Automatic water softeners

Automatic softeners with ALIA valve



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS1945	5 lt	3,5 lt	1500 lt/h 10 kg		0,6 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-30°C	230x360x515 mm
OS1946	8 lt	5,6 lt	1500 lt/h 20 kg		1,0 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-30°C	250x460x540 mm
OS1947	12 lt	8,5 lt	1500 lt/h 25 kg		1,5 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-30°C	285x405x595 mm

Automatic softeners GIX

TIMED with Autotrol valve 255
Logix 740



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2457	5 lt	3,5 lt	1500 lt/h 10 kg		0,6 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	230x385x515 mm
OS1079	8 lt	5,6 lt	1500 lt/h 20 kg		1,0 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	245x450x540 mm
002454* 8 lt pnc 921305		5,6 lt	1500 lt/h 20 kg		1,0 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	245x450x540 mm
OS2458	12 lt	8,5 lt	1500 lt/h 25 kg		1,4 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	285x425x650 mm

*Water softener coated with stainless steel panels

Amount of softened water based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS1945 / OS2457	1050	700	525	420	350
OS1946 / OS1079 / 002454	1680	1120	840	672	560
OS1947 / OS2458	2520	1680	1260	1008	840

Automatic water softeners

Automatic softeners
TIMED cabinet
with Autotrol valve 255
Logix 740



Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS1083	12 lt	8,5 lt	1500 lt/h	25 kg	1,4 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	320x500x660 mm
OS1089	24 lt	17 lt	1500 lt/h	50 kg	2,7 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	320x500x1120 mm

Amount of softened water
based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS1083	2520	1680	1260	1008	840
OS1089	5040	3360	2520	2016	1680

Automatic softeners
LARGE SERIES VOLUMETRIC
with valve Autotrol 255 Logix 760



Cylinder Brine

Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2459	50 lt 10"x44"	35 lt	1500 lt/h	120 kg	7,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø271x1300mm Brine: Ø541x810mm
OS2460	84 lt 13"x44"	59 lt	1500 lt/h	120 kg	12,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø360x1300mm Brine: Ø541x810mm

Amount of softened water
based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS2459	10500	7000	5250	4200	3500
OS2460	17640	11760	8820	7056	5880

Automatic water softeners

Automatic softeners
LARGE SERIES PERFORMA VOLUMETRIC
with valve Autotrol 268 Logix 760



Cylinder Brine

Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2461	24 lt 8"x35"	17 lt	4000 lt/h	80 kg	2,7 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø219x1060mm Brine: Ø480x660mm
OS2462	50 lt 10"x44"	35 lt	4000 lt/h	120 kg	7,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø271x1300mm Brine: Ø541x810mm
OS2463	84 lt 13"x44"	59 lt	4000 lt/h	120 kg	12,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø360x1300mm Brine: Ø541x810mm

Automatic softeners
LARGE SERIES PERFORMA TIMED
with valve Autotrol 268 Logix 740



Cylinder Brine

Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2464	24 lt 8"x35"	17 lt	4000 lt/h	80 kg	2,7 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø219x1060mm Brine: Ø480x660mm
OS2325	50 lt 10"x44"	35 lt	4000 lt/h	120 kg	7,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø271x1300mm Brine: Ø541x810mm
OS2326	84 lt 13"x44"	59 lt	4000 lt/h	120 kg	12,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø360x1300mm Brine: Ø541x810mm

Amount of softened water
based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS2461 / OS2464	5040	3360	2520	2016	1680
OS2462 / OS2325	10500	7000	5250	4200	3500
OS2463 / OS2326	17640	11760	8820	7056	5880

Manual water softeners

Manual water softeners



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Salt for regeneration cycle	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OC1903	8 lt	5,6 lt	1000 lt/h	1,0 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x400 mm
OS0330	12 lt	8,4 lt	1000 lt/h	1,5 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x515 mm
OS0329	20 lt	14 lt	1000 lt/h	2,5 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x900 mm

Manual water softeners "by pass"



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Salt for regeneration cycle	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS1074	8 lt	5,6 lt	1000 lt/h	1,0 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x400 mm
OS1076	12 lt	8,4 lt	1000 lt/h	1,5 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x500 mm

Amount of softened water based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OC1903 / OS1074	1680	1120	840	672	560
OS0330 / OS1076	2520	1680	1260	1008	840
OS0329	4200	2800	2100	1680	1400

Water softeners consumables



OL1140
Water filter NK111
 with wound cartridge 50µm.
 Recommended for manual
 water softeners.
 Ø 5", Coupling 3/8" G

OL1141
Water filter NK112
 with wound cartridge 50µm.
 Recommended for manual
 water softeners.
 Ø 5", Coupling 3/4" G

OS1027
Wound cartridge 5" 50µm
 Ø 61 H 127 mm
 for OL1140 and OL1141

OS2250
Carbon block cartridge 5µm
 for OL1140 and OL1141

OS1027



005480

OS1423
Complete filter NK223C
 with carbon block cartridge
 5µm.
 Recommended for manual
 water softeners.
 Ø 9, Coupling 1/2" G m/f

OS1029
Wound cartridge 9" 50µm
 Ø 61 H 247 mm
 for OS1423

005480
Carbon block cartridge 5µm
 for OS1423



OS2165
Salt for water softener
 25 kg package



Cationic Resin
 suitable for all softeners with
 use of resin, of any capacity

OS2191
 5 kg package (lt 6,14)

OS2192
 10 kg package (lt 12,28)

OS0333
 25 kg package (lt 30,71)



OS1090
**Resin sanitiser for automatic
 water softeners**
 ▶ resin disinfection device for
 Autotrol 255 Logix valve with
 salt alarm
 ▶ water softeners codes
 OS1079-OS1083-OS1089



OS2245
**Watertight pH/EC/TDS/
 Temperature meter – scale
 EC/TDS low**

Pocket watertight instrument for:
 ▶ pH/EC/TDS/ (3999 µS/cm,
 2000 ppm)
 ▶ temperature 0: 60°C
 ▶ scale EC/TDS low



OS1701
Total carbonate hardness kit



002453
Resin sanitizer
 for water softener



▶ Floating watertight body.
 ▶ Replaceable pH electrode
 with renewable fibre junction
 with a large display with two
 levels of reading and auto
 shutoff in case of inactivity.
 ▶ The instrument comes
 complete with protective
 hood, electrode
 replacement key, batteries
 and instructions.
 ▶ Dim.mm 163 x 40 x 26 mm
 ▶ Weight: 100 g

Water treatment

Purity C Quell ST



OS1628

Purity C 150 Quell ST System

- ▶ Capacity 2408 l at 10° dH with bypass 40% (coffee machines)
- ▶ Capacity 1656 l at 10° dH with bypass 10% (ovens)
- ▶ Working temp. 4°C-30°C
- ▶ Min/max pressure 2-8.6 bar
- ▶ Head connections 3/8"
- ▶ Dim. Ø117x417h, complete with digital flow meter (OS2555), water hardness test (OS1701) and head with bypass (OS1638)



OS1629

Purity C 300 Quell ST System

- ▶ Capacity 4000 l at 10° dH with bypass 40% (coffee machines)
- ▶ Capacity 2750 l at 10° dH with bypass 10% (ovens)
- ▶ Working temp. 4°C-30°C
- ▶ Min/max pressure 2-8.6 bar
- ▶ Head connections 3/8"
- ▶ Dim. Ø125x464h, complete with digital flow meter (OS2555), water hardness test (OS1701) and head with bypass (OS1638)



OS1630

Purity C 500 Quell ST system

- ▶ Capacity 6800 l at 10° dH with bypass 40% (breakfasts)
- ▶ Capacity 4675 l at 10° dH with bypass 10% (ovens)
- ▶ Working temp. 4°C-30°C
- ▶ Min/max pressure 2-8.6 bar
- ▶ Head connections 3/8"
- ▶ Dim. Ø149x553h, complete with digital flow meter (OS2555), water hardness test (OS1701) and head with bypass (OS1638)



OS1631

Purity C 1100 Quell ST System

- ▶ Capacity 11,500 l at 10° dH with bypass 40% (breakfasts)
- ▶ Capacity 7906 l at 10° dH with bypass 10% (ovens)
- ▶ Working temp. 4°C-30°C
- ▶ Min/max pressure 2-8.6 bar
- ▶ Head connections 3/8"
- ▶ Dim. Ø184x553h, complete with digital flow meter (OS2555), water hardness test (OS1701) and head with bypass (OS1638)

Water treatment

Purity C Quell ST System accessories and replacement cartridges



OS1054

Cartridge Purity C 150 Quell ST

OS1055

Cartridge Purity C 300 Quell ST



OS1056

Cartridge Purity C 500 Quell ST

OS1708

Cartridge Purity C 1100 Quell ST



OS1892

Service cartridge Purity C
for cleaning, disinfection
and descaling of equipment
directly connected.

- ▶ Ø 125 mm - H 233 mm
- ▶ Maximum cartridge capacity 0.5 l
- ▶ Operating pressure 0.5-8.6 bar
- ▶ Temp. water inlet 4-30 ° C
- ▶ The cartridge does not include the head OS1638



OS2555

Digital volumetric litre counter

- ▶ Flow meter 10-100A
- ▶ Flow rate 10-100 l/h
- ▶ Temp. 4°C-30°C; max 8 bar
- ▶ Indicates the remaining litres the filtration system can treat
- ▶ Battery powered



OS1638

Head with bypass
variable 0%-70%
and rinsing valves
male connections 3/8"

OS2123

Brita PURITY C reduction kit
3/4"-3/8" Set of 2 pieces



OS2132

Cartridge

Filter Purity C 1000 AC
Ideal for vending machines
for cold and hot drinks

OS2226

Set of 20 cartridges
Purity C 1000 AC

Water treatment

Purity STEAM for OVENS



- OS1632**
Purity STEAM 450 filter
 with MDU - litre counter
 system included
- ▶ Capacity 3,680 l at 10° dH with bypass at pos.1
 - ▶ Working temp. 4°C-30°C
 - ▶ Max press. 6.9 bar
 - ▶ Inlet/outlet head connections G1" - G3/4"
 - ▶ Dim. Ø249x408h



- OS1633**
Purity STEAM 600 filter
 with MDU - litre counter
 system included
- ▶ Capacity 5,771 l at 10° dH with bypass at pos.1
 - ▶ Working temp. 4°C-30°C
 - ▶ Max press. 6.9 bar
 - ▶ Inlet/outlet head connections G1" - G3/4"
 - ▶ Dim. Ø249x520h



- OS1634**
Purity STEAM 1200 filter
 with MDU - litre counter
 system included
- ▶ Capacity 10,800 l at 10° dH with bypass at pos.1
 - ▶ Working temp. 4°C-30°C
 - ▶ Max press. 6.9 bar
 - ▶ Inlet/outlet head connections G1" - G3/4"
 - ▶ Dim. Ø249x550h

Purity STEAM System accessories and replacement cartridges

OS1635



- OS1635**
 Purity STEAM 450 cartridge
- OS1636**
 Purity STEAM 600 cartridge
- OS1637**
 Purity STEAM 1200 cartridge

Purity C STEAM for ovens



- OS2491**
PURITY C 500 STEAM kit
 complete with cartridge
 (OS2490) and head (OS2489)



- OS2492**
PURITY C 1100 STEAM kit
 complete with cartridge
 (OS2488) and head (OS2489)

Accessories Purity C STEAM for ovens and replacement cartridges



- OS2490**
 Cartridge PURITY C 500
 STEAM



- OS2489**
 Head PURITY C STEAM
 3/8" M

- OS2488**
 Cartridge PURITY C 1100
 STEAM



- OS1701**
 Total carbonate hardness kit

Water treatment

Purity Clean and Clean Extra



- OS0801**
PURITY 1200 CLEAN filter system
with PARTIAL demineralisation including filter cartridge.
- Connections: inlet G1"- outlet G3/4"
 - Min./max inlet pressure: 2-6 bar
 - Working temperature 4°-60°C
 - Capacity: 13.000 l at 10° KH



- OS0803**
PURITY 1200 EXTRA filter system
with TOTAL demineralisation including filter cartridge.
- Connections: inlet G1"- outlet G3/4"
 - Min./max inlet pressure: 2-6 bar
 - Working temperature 4°-60°C
 - Capacity: 5.000 l at 10° KH

Purity CLEAN and CLEAN EXTRA System accessories and replacement cartridges



- OS0802**
PURITY 1200 CLEAN cartridge



- OS0804**
PURITY 1200 CLEAN EXTRA cartridge



- OS2555**
Digital volumetric litre counter
- Flow meter 100-100A
 - Flow rate 10-100 l/h
 - Temp. 4°C - 30°C max 8 bar
 - Indicates the remaining litres the filtration system can treat
 - Battery powered



- OS1223**
Head for Purity CLEAN and CLEAN EXTRA with bypass

- OS2556**
Digital volumetric litre counter
- Flow meter 100-700A
 - Flow rate 100-700 l/h

Purity AquaQuell System accessories and replacement cartridges

OS0797



- OS0797**
Purity AquaQuell 450 cartridge

- OS0798**
Purity AquaQuell 600 cartridge

- OS0683**
Purity AquaQuell 1200 cartridge

Water treatment with reverse osmosis system

Reverse osmosis filtration system with atmospheric boiler



OS1822

Reverse osmosis filter

- Supply voltage: 220 ... 240 V / 1N ph / 50/60 Hz
- Power consumption 0.18kw
- feed water pressure: 1 - 4 bar
- Water temperature of
- Power supply: 5-35 ° C
- Water inlet pipe dimensions: 3/4 "



OL1140

Water filter NK111

with wound cartridge 50µm.
Recommended for manual water softeners. Ø5", Coupling 3/8" G

OS2250

Carbon block cartridge 5µm
for OL1140 and OL1141



OS1821

Replacement filter cartridge
for osmosis



OPRAH2

Wheels for reverse osmosis filter

Kit of 4 pcs

OS1826

Head with wall bracket



OPRY39

Container

for filter membrane 3012
connection 1/4 "- 3/8"
(membrane not included)



OS1848

Filter membrane 3012
300 GPD

Spare parts for reverse osmosis filter RO600C



OS0730

Descaler kit for

osmosis membrane cleaning
Complete with 2 carbon filters
and 1 descaling agent
200gr

OS0728

Carbon filter
for RO600C



OS0735

Pump filter with membranes
for RO400/600"

OS0738



OS0738

Pump kit RO600

OS0736

Protective bushing

OS0737

Motor RO600 23V





Pumps for detergents

Index

Pumps for food segment	page 46
Pumps for laundry segment	page 48



Purchase our detergents and accessories
at electroluxprofessional.com

Pumps for food segment



Peristaltic pump for detergent

model PR4 with analogic dosing regulation
squeeze tubes made in santoprene
used as accessory for the dishwashers
without built-in dosing systems

- ▶ Easy regulation
- ▶ Supplied with fixing bracket, injection connection, suction tube, outlet tube and filter

Code	Compatible with
OS0669	glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system

- ▶ Power consumption: 3,5w
- ▶ Power supply: 230V, 50Hz
- ▶ Pressure: 0,1 bar
- ▶ Flow: 0,6 - 4l/h



Fixed speed peristaltic pump for detergent

model PR6 with analogic dosing regulation
by conductivity probe, squeeze tubes made
in santoprene

- ▶ Used as accessory for the dishwashers without built-in dosing systems
- ▶ Easy regulation
- ▶ Supplied with fixing bracket, injection connection, suction tube, outlet tube filter and conductivity probe

Code	Compatible with
OS0670	glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system

- ▶ Power consumption: 3,5w
- ▶ Power supply: 230V, 50Hz
- ▶ Pressure: 0,1 bar
- ▶ Flow: 6l/h



Peristaltic pump for rinse aid

model PR1 with analogic dosing regulation
tubes made in Sekobril

- ▶ Used as accessory for the dishwashers without built-in dosing systems
- ▶ Easy regulation
- ▶ Supplied with fixing bracket, injection connection with non-return valve, suction tube, outlet tube, filter, pipe connection of "fi" 6-8 mm, for single tank machines

Code	Compatible with
OS0671	glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system

- ▶ Power consumption: 3,5w
- ▶ Power supply: 230V, 50Hz
- ▶ Pressure: 3 bar
- ▶ Flow: 0,2 - 1l/h



0U1032

Dosing pump G200

230V 50Hz;
detergent flow rate 0.777g/sec,
max flow rate 2 l/h



OS0672

Dosing system TWINDOSE 40

- ▶ Microprocessor control with LCD display
- ▶ Detergent dosing - conductivity or timed
- ▶ Rinse aid dosing - speed or timed
- ▶ Detergent pump: santoprene tube flow rate 12.5 l/h
- ▶ Rinse aid pump: SekoBril tube
- ▶ Flow rate 2.5 l/h 3 bar
- ▶ Max absorb. 20 W
- ▶ Switching power supply from 80 to 265 Vac 50Hz for tunnel machines

Pumps for food segment



OL3182

Rinse aid dispenser

- Flow adjustment screw
- From 0 to 4 cm³/cycle complete with
- Hose connectors
- Bottom filter with bushing in steel and tube



OL3200

Rinse aid dispenser

- Flow adjustment screw
- From 0 to 4 cm³/cycle



OHA055

Rinse aid dispenser

type 1000



OHA056

Rinse aid dispenser

type 3000 with filter



OS2285

Rinse aid peristaltic pump model PG 0.4

- Flow rate: 0.4 l/h
 - Pressure: 3 bar
 - Power supply: 230 V - 50/60 Hz
- complete with:
- 4 m PE tube 4x6, filter and bottom weight, rinse aid
 - Injection valve
 - ROHS certification



OS1986

Detergent peristaltic pump model PG 3

- Flow rate: 3 l/h
 - Pressure: 0.1 bar
 - Power supply: 230V - 50/60 Hz
- complete with:
- 4 m PE tube 4x6,
 - filter and bottom weight,
 - passwall
 - ROHS certification



OS0706

Rinse aid peristaltic pump model NBR 0.4

- Flow rate reg. t/p: 0.4 l/h
 - Pressure: 3bar
 - Power supply: 230V- 50Hz
- complete with:
- 2 m suction pipe
 - 2 m delivery pipe, s/steel bottom weight and filter, injection connection with non-return valve for rinse aid
 - ROHS certification



OS1987

Detergent peristaltic pump model NBR 3

- Flow rate reg. t/p : 3 l/h
 - Pressure: 0.1 bar
 - Power supply: 230V - 50 Hz
- complete with
- pipes and connections
 - ROHS certification

Pumps for laundry segment



*Suitable for all the ClarusVibe models



Jetsave

Venturi pumps, designed for easy installation, easy programming, easy savings, enhance the accuracy of chemical delivery while reducing costly system maintenance.

- ▶ **ClarusVibe:** Electrolux Professional washer extractors with ClarusVibe control.
- ▶ **Save on chemicals:** impossible to avoid chemical savings, never overuse chemicals again.
- ▶ **Easy installation:** plug&play connection from washers. No need to open the washer's panels for wiring.
- ▶ **Easy programming:** all is managed by ClarusVibe from washers in ml/kg. No need extra PC with dedicated software installed.
- ▶ **Flexible pumps extension:** available for 2, 3, 4, 5, 6, 8 or 10 products, while if more needed, easily fit up to 15 pumps via modular extension.
- ▶ **Low level alarm:** always a step ahead when the chemical is running low. A warning message appears on the washers' ClarusVibe screen.
- ▶ **Statistics management:** All dosing reports/ statistics can be download directly from washer and easily monitor the savings.
- ▶ **Less maintenance:** no moving parts or squeeze tubes to wear out
- ▶ **Consistent dosage:** No drop-off, even over a long period of time.
- ▶ **Easier & tidier installation:** built-in flush manifold.

Code	PNC	Description
1LSMZP	988930001	Complete kit with 2 pumps, 550 ml/min
1LSMZR	988930002	Complete kit with 3 pumps, 550 ml/min
1LSMZS	988930003	Complete kit with 4 pumps, 550 ml/min
1LSMZK	988930004	Complete kit with 5 pumps, 550 ml/min
1L827F	988930005	Complete kit with 6 pumps, 550 ml/min
1L827G	988930006	Complete kit with 8 pumps, 550 ml/min
1L827H	988930007	Complete kit with 10 pumps, 550 ml/min

- ▶ Power supply from the washer extractor 100-240V 50-60Hz /0.1A (Max)
- ▶ Water supply: Min 1.8bar - Max 6bar



*Suitable for all the ClarusVibe models



Dosave

Peristaltic pumps, with external easy connection box from washer extractors, designed for easy installation, easy programming, easy savings:

- ▶ **ClarusVibe:** Electrolux Professional washer extractors with ClarusVibe control.
- ▶ **Save on chemicals:** never overuse chemicals again.
- ▶ **Easy installation:** plug&play connection from washers. No need to open the washer panels for wiring.
- ▶ **Easy programming:** all is managed by ClarusVibe from washers in ml/kg. No need extra PC with dedicated software installed.
- ▶ **Flexible pumps extension:** available for 2,3,4,5 products, while if more needed, easily fit up to 15 pumps via modular extension.
- ▶ **Low level alarm:** always a step ahead when the chemical is running low. A warning message appears on the washers' ClarusVibe screen.
- ▶ **Statistics management:** All dosing reports/ statistics can be download directly from washer and easily monitor the savings.

Code	PNC	Description
1LSMZT	988930011	Complete kit with 2 pumps, Silicone tubes, 350 ml/min
1LSMZU	988930012	Complete kit with 3 pumps, Silicone tubes, 350 ml/min
1LSMZV	988930013	Complete kit with 4 pumps, Silicone tubes, 350 ml/min
1LSMZW	988930014	Complete kit with 5 pumps, Silicone tubes, 350 ml/min

- ▶ Power supply from the washer extractor 220-240V 50-60Hz /3A (Max)
- ▶ Water supply (flush manifold): Min 1.8bar - Max 6bar

Pumps for laundry segment



*Suitable for all the Compass Pro models



EDS – Efficient Dosing System

Efficient Dosing System automatically adjusts the quantity of detergent to the real load of your Electrolux Professional washer extractor.

- ▶ Compatible with Electrolux Professional Laundry washer extractors equipped with Compass Control, Compass Pro or Clarus Control
- ▶ Knows the selected program directly from the washer extractors control panel
- ▶ Variable temperature and time process validation to fulfill different hygiene regulation in different countries
- ▶ Integrated USB port to collect statistics and monitor easily the savings
- ▶ PC software to prepare the formulas an upload in the controller via a USB memory for an easy installation
- ▶ 350 ml squeeze tube for a fast dosing of detergent
- ▶ Made on measure for Electrolux Professional Compass Control®, Compass Pro® and Clarus Control® all connections delivered with the apparel for an easy and quick installation
- ▶ Available in 2, 3, 4, 5 or 6 pumps version to match any kind of application

Code	PNC	Description
1L081P	988916901	Complete kit with 2 pumps: 230V 50/60Hz
1L081V	988916911	Complete kit with 2 pumps: 115V 60Hz
1L081R	988916902	Complete kit with 3 pumps: 230V 50/60Hz
1L081W	988916912	Complete kit with 3 pumps: 115V 60Hz
1L081S	988916903	Complete kit with 4 pumps: 230V 50/60Hz
1L081X	988916913	Complete kit with 4 pumps: 115V 60Hz
1L081T	988916904	Complete kit with 5 pumps: 230V 50/60Hz
1L081Y	988916914	Complete kit with 5 pumps: 115V 60Hz
1L081U	988916905	Complete kit with 6 pumps: 230V 50/60Hz
1L081Z	988916915	Complete kit with 6 pumps: 115V 60Hz



*Suitable for all the Compass Pro models



ED Venturi

Combines the best of EDS with the best of Venturi pumps to automatically adjust the quantity of detergent to the real load of your Electrolux Professional washer extractor, delivering the best wash result in a sustainable way together with a low maintenance, venturi-based, water-powered laundry unit.

- ▶ Compatible with Electrolux Professional Laundry washer extractors equipped with Compass Control®, Compass Pro® or Clarus Control®
- ▶ 3, 5 or 6 chemical products in a single cabinet
- ▶ Chemical saving: thanks to our unique Automatic Saving and Efficient Dosing controller
- ▶ Low maintenance - No peristaltic tubes, no routine maintenance, low total installed cost, no moving parts
- ▶ Wide range of consistent output - 500ml/min or 1500ml/min
- ▶ Integrated flushing manifold for long distance delivery
- ▶ Integrated USB port to collect statistics and monitor easily the chemical savings
- ▶ PC software to prepare the formulas and upload in the controller via a USB memory for an easy installation

Code	PNC	Description
1LSNCG	988930024	ED Venturi 3 PROD LF Low Flow 500ml
1LSNCF	988930023	ED Venturi 3 PROD HF High Flow 1500ml
1LSNCE	988930022	ED Venturi 5 PROD LF Low Flow 500ml
1LSNCD	988930021	ED Venturi 5 PROD HF High Flow 1500ml
1LSPES	988930025	ED Venturi 6 PROD LF Low Flow 500ml
1LSPET	988930026	ED Venturi 6 PROD HF High Flow 1500ml





Installation material for laundry

Index

Hoses and interfaces	page 54
Cables, connections	page 55



Purchase our detergents and accessories
at electroluxprofessional.com

Installation material for laundry



0W1W4B
432930031
EPDM hose 350ml/min
Suitable for EDS and Dosave
Qty: 1



0W1W4D
432930033
EPDM hose 500ml/min
Suitable for EDS and Dosave
Qty: 1



0W1W4C
432930032
Silicone hose 350ml/min.
Suitable for EDS and Dosave
Qty: 1



0W1W4E
432930034
Silicone hose 500ml/min
Suitable for EDS and Dosave
Qty: 1



0W7TRD
432930052
EVA tube
Used in installations of
automatic dosing
Length: 15 m
3/8" ID X 1/2" OD



0W7TRC
432930051
EVA Tube
Used in installations of
automatic dosing
Length: 25 m
3/8" ID X 1/2" OD



1L0GDY
988916621
Low level alarm
With three hose connections



1LSN8T
988930031
ID interface
For 3rd party pumps

1LRZ0E
988916610
Low level alarm
With one hose connection



1L0AY1
988916920
EDS flush manifold
For 4 products

1L0GC3
988916955
EDS extension
For flush manifold for
4 products

Installation material for laundry



0W23RJ
432731048
Dip tube with check valve
For EDS
1 pcs



0W7TRL
432930071
Extension power cable (6m).
Recommended to Jetsave & Dosave.
Product pnc: 988916974



0W7TRM
432930072
Extension data cable (6m).
Recommended to Jetsave & Dosave.
Product pnc: 988916975



0W7TPC
432930083
Extension signal cable (10m)
Suitable for Jetsave.



0W7VNE
432930093
Quick connections
1/2" Straight connection.
Recommended to all pumps
when connecting hoses
Quantity: Set of 10 pcs



0W7VNB
432930089
Quick connections
1/4" Barb x 1/2" Pushfit.
Recommended to EDS & Dosave to connect container to pump
Quantity: Set of 10 pcs



0W7VNC
432930090
Quick connections
1/2" Tee Piece.
Recommended to all pumps
when connecting chemical
to several hoses
Quantity: Set of 10 pcs



0W7VND
432930092
Quick connections
1/2" Elbow.
Recommended to all pumps
when connecting hoses
Quantity: Set of 10 pcs

Safety at glance

QR code

All Electrolux Professional detergents present a label QR code for immediate safety data sheet download



Safety Data Sheet

Safety Data Sheets are compatible with all devices (i.e. smart phones, tablets, computers).

Just select your Country and the proper SDS will be immediately available to you.



A safety data sheet, or SDS, is a standardized document that contains safety and health data, chemical properties, health and environmental hazards, protective measures, as well as safety precautions for storing, handling, and transporting detergents .

C25 Rinse & Descale
Safety Data Sheet
According to Regulation (EC) No. 1272/2008 (CLP) and to European Regulation (EC) No. 609/2004
Date of issue: 10/04/2019
Issue no.: 0013 - 0019

SECTION 1: Identification of the substance/mixture
Product name: C25 Rinse & Descale
Product number: 10170000000000000000
Use of the substance/mixture: For professional use

SECTION 2: Hazards identification
Classification according to Regulation (EC) No. 1272/2008 (CLP):
Hazard statements (CLP): H302, H312, H332
Precautionary statements (CLP): P201, P202, P273, P501

SECTION 3: Composition/information on ingredients
No additional information available

SECTION 4: First aid measures
Not applicable

SECTION 7: Handling and storage
Not applicable

SECTION 8: PPE
Not applicable

SECTION 9: Physical and chemical properties
Not applicable

SECTION 14: Transport information
Not applicable

Safety data sheets have sixteen sections; here the list of the sections you may be more interested in:


- Section 1** Product identifier and Emergency telephone numbers
- Section 3** Composition
- Section 4** First aid measures
- Section 7** Handling and storage
- Section 8** PPE
- Section 9** Physical and chemical properties
- Section 14** Transport Information

Virus: scientific studies on inactivation^{(1),(2)}

Combining our appliances to our selected chemicals grants a valid and effective solution to provide you, your customers and your staff with the confidence that their well-being is safeguarded at all times.

Infectivity of Coronavirus is sensitive^{(1), (2)} to:

- **Detergents with extreme pH values** (highly acid or highly alkaline)
- **High temperature exposure** for a certain period of time



* Logarithmic scale of coronavirus concentration after chemical substance and temperature exposure. Please note that safety is below the concentration line of log₁₀(1) which corresponds to zero units.

(1) M. E. R. Darnell et al., Inactivation of the coronavirus that induces severe acute respiratory syndrome, SARS-CoV, Journal of Virological Methods 121 (2004) 85-91

(2) Bio Basic Europe, Bibliographic verification aimed to assess the virucidal efficacy of processes and products used during washing and rinsing cycles with Electrolux Professional dishwasher, 17th July 2020



Accessories for protection and prevention



OS2644
Face mask with filter FFP2
 Foldable single-use with EN149 valve. Adjustable aluminum nose piece.
 PPE class III,
 EN 149:2001 + A1:2009
 Single pack



OS2646
Face mask with filter FFP2
 Foldable single-use without valve; nose part with flexible insert
 EN 149:2001 + A1:2009
 Pack of 10 pieces



OS2659
Protective visor
 Face shield with 90° opening protective visor
 • visor in PET, thickness 0.8mm
 • dimensions: 250mm x 310mm
 • front strip with polyethylene pad
 • polyester rear elastic
 • in accordance with standard EN 166
 • Category II PPE



Thick blue nitrile glove
 • Ambidextrous and reusable
 • Excellent mechanical and chemical resistance to detergents, abrasive cleaning agents, oils and greases
 • Excellent tactile sensitivity, dexterity and elasticity
 • Thickness 0.23mm
 • Category III
 EN388:E362016
 EN ISO 374-1:2016
 EN ISO 374-5:2016
 • Pack of 2 pieces



OS2653
Clear goggles OX3000
 Wrap-around, can be worn over prescription eyewear
 Anti-fogging coating
 UV protection cert. EN170
 EN166 Certification
 Class II PPE

OS2674 size S
OS2675 size M
OS2676 size L
OS2677 size XL



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable – and truly sustainable every day.

Follow us on



www.electroluxprofessional.com

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated with the environmental needs of our customers in mind
- ▶ Our technology is RoHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

